



# RCT 2299-2 - 2320-2

Open cooling towers

## Engineering data

**REMARK:** Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

### General notes

1. Access door is always opposite to inlet connection end.
2. Alternative inlet/outlet and tower configurations are available.
3. Nominal outlet connection size provided.
4. Actual outlet sized to match flow.
5. Models RCT 2218-1 and 2129-1 have direct drive motors.
6. Models RCT 2218-2 and 2129-2 have direct drive motors.
7. Triple fan units are not available with common FRP basin. Only for installation on concrete basin.

**Last update:** 01/01/2025

**RCT 2299-2 - 2320-2**



1. Water inlet; 2. Water outlet; 3. Drain; 4. Overflow; 5. Make up; 6. Quick fill; 7. Fan motor.



Model	Weights (kg)			Dimensions (mm)			Air Flow (m <sup>3</sup> /s)	Fan Motor (kW)	Fluid Inlet ND (mm)
	Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H			
<b>RCT 2299-2</b>	<b>11450</b>	<b>4200</b>	<b>2100</b>	<b>6985</b>	<b>3499</b>	<b>4019</b>	<b>78.1</b>	<b>(2x) 15.0</b>	<b>(2x) 200</b>
<b>RCT 2320-2</b>	<b>11450</b>	<b>4200</b>	<b>2100</b>	<b>6985</b>	<b>3499</b>	<b>4019</b>	<b>83.5</b>	<b>(2x) 18.5</b>	<b>(2x) 200</b>